

Application:

Electric washer, gasoline or diesel washer, large industrial washer.

Construction:

Tube: NBR synthetic rubber.

Reinforcement: One or two braided high tensile steel wire.

Cover: NBR oil and weather resistant synthetic rubber.

Color:

Black

Temperature:

-40°C to +100°C

Standard: SAE/DIN

High Pressure Washer Hose



Item Code	Inner Diameter		Outer Diameter	Working Pressure		Burst Pressure		Min Bend Radius	Length	Weight
	inch	mm		mm	mpa	psi	mpa			
1S-04	1/4	6.4	12.0	21	3263	84	13050	102	100	0.24
2S-04	1/4	6.4	15.0	40	5800	160	23200	102	100	0.40
1S-05	5/16	7.9	15.1	21.5	3120	86	12480	114	100	0.30
2S-05	5/16	7.9	16.5	35	5075	140	20300	114	100	0.47
1S-06	3/8	9.5	17.5	18	2615	72.1	10460	127	100	0.37
2S-06	3/8	9.5	19.1	33	4800	132	19200	127	100	0.55

Joint Connection:

1. Metric female waterwash inserts (Metric system 20011-T

20111-T



2. Other fittings please advise, if it is not standard, please supply specific standard parameters or detailed drawing.



Office Address:

B-702
Hangzhou Smart Industry Park
No. 857 Wenyixi Rd.
Hangzhou 310030
CHINA

Registered office

Hangzhou

Internet Address

www.flexiblerubberhoses.com

Telephone

86-571-81023091

Telefax

86-571-81023093

Email (Janet Yao)

ps005@parshun.com

Skype

paishun005